

PIN#

SL-NT-C NON-TOXIC CRYOGENIC GREASE

PRODUCT DESCRIPTION

SL-NT-C is the newest member of the well known Sentinel family of food grade lubricants.

SL-NT-C is a multi-purpose synthetic, extreme low temperature, non-toxic, water white, tasteless, and odorless grease. SL-NT-C is a synthetically thickened grease which employs an extremely low viscosity polyalphalfin (PAO) based fluids.

Its low Temperature torque characteristic at -73°C (-100°F) is a functional benefit that conventional greases can not achieve.

SL-NT-C complies with FDA regulations Title 21, CFR 178.3570 and is authorized by the USDA for use in federally inspected meat and poultry plants. SL-NT-C has received an H-1 rating.

06540

TYPICAL CHARACTERISTICS

NLGI Grade	$1^{1/2}$	ASTM D-1092
Worked Penetration	290-315	ASTM D- 217
Dropping Point	None	ASTM D-2265
Oxidation Stability Psi Drop @ 100 hrs	-2	ASTM D- 942
Rust Preventative	1a	ASTM D-1743
Water Washout	2.0	ASTM D-1264
Extreme Pressure Timken OK Load Kg (Lb)	20+ (45)	ASTM D-2509
Four Ball Wear	.7mm	ASTM D-2266
USDA Rating	H-1	
Appearance	Clear, Smooth	

TO ORDER OR FOR ADDITIONAL INFORMATION



EL SALVADOR

Av. Siemens, Lote No. 3, Urb. Industrial Santa Elena, Ant. Cuscatlan, La Libertad

Tel. (503) 2212-6300 Fax (503) 2289-0367

GUATEMALA

Calle Real de Guajitos, Lote No. 147, Zona 12, Col. Morse, Ciudad de Guatemala Telefax: (502) 2383-4047 * 2383-4048

This file was made with a DEMO version of PDFtypewriter. You can purchase the full version which does not display this message at http://www.ctdeveloping.com
This document was created with Win2PDF available at http://www.daneprairie.com . The unregistered version of Win2PDF is for evaluation or non-commercial use only.